

# AONT-1532

## GPON SFU/HGU ONT (4GE+2POTS+RF)

### Feature Summary

- ◆ ITU-T G.984 and G.988 compliant, BBF.247 ready
- ◆ BBF TR.156 N:1 (E-Tree), 1:1 (E-Line) and E-LAN VLAN Model compliant
- ◆ Indoor wall or table mount
- ◆ Four 10/100/1000Base-T Ethernet RJ-45 ports
- ◆ Two FXS POTS ATA RJ-11 ports
- ◆ One coaxial F-connector RF video port
- ◆ Configurable for either Ethernet Bridged mode or Gateway Routed mode operation
- ◆ Built-in L2 wire-speed switch with dynamic bridging, 4K VLANs (Untagged, Priority tagged, Port based, 802.1q single tagged, 802.1ad (Q-in-Q) double tagged)
- ◆ ToS/DSCP to 802.1p mapping
- ◆ Flexible traffic mapping, policing & shaping
- ◆ VoIP features: SIP, multiple voice codecs, T.30 and T.38 Fax, various CLASS services
- ◆ Supports feature rich VoIP application profiles for Caller ID, Call progress, Call Waiting, Call Direct, and Call presentation
- ◆ Integrated router with features such as IPv4, IPv6, IPoE, PPPoE, NAT, DHCP, DNS, IP Filtering, IP forwarding, Static IP routing, IP QoS and Firewall
- ◆ Supports dual software image - working image & alternative image for image rollback
- ◆ Serial number or ID and password based activation and authentication
- ◆ IGMPv2/v3 (IPv4) and MLDv2 (IPv6) snooping, proxy and filtering, 256 multicast groups
- ◆ Web based GUI for local provisioning and software upgrade
- ◆ Dual managed by ITU-T G.988 OMCI and/or remote management functions as TR-069 and Telnet for provisioning, diagnostics, monitoring, and software upgrade
- ◆ Battery Backup ready with an 8-pin (4x2) 'UPS' connector on rear
- ◆ ON/OFF and factory default RESET pushbuttons



### Applications

The AONT-1532 has been optimized for residential homes for providing triple play Broadband services that also require RF video.

#### Advanced High Bandwidth GPON technology

The AONT-1532 is fully FSAN (ITU-T G.984) compliant 2.488 Gbps downstream and 1.244 Gbps upstream GPON systems.

#### Quality of Service

The AONT-1532 supports extensive QoS features, including 802.3x - flow control, DSCP to 802.1p mapping, upstream congestion control, and downstream traffic scheduling for premium or time sensitive content. Intelligent and robust buffer and queue management for Ethernet traffic, with individual prioritized queues, ensures that tiered service offerings based on different bit-rates and QoS can be readily supported.

#### Gateway

The AONT-1532 contains both wire-speed L2 switch and L3 routing gateway with port forwarding, NAT and NAPT address translation, built-in PPPoE support for HSI, and an integrated stateful packet inspection (SPI) firewall with a configurable access control list (ACL) and application-level gateway (ALG). Support for VPN (L2TP, PPTP and IPSec) pass through is also provided. Included as part of the gateway function are DHCP client, DHCP server and DNS server for IPv4 and IPv6.

#### Security

The AONT-1532 comes with the latest security features, including MAC address spoofing protection, MAC/IP address port binding, per-port access control list (ACL) based on port, MAC address and Ether-type, DoS prevention and wireless encryption protocols such as WEP and the more secure WPA/WPA2.

#### Flexible Management

The AONT-1532 is managed from the AOLT-4000 and AOLT-4200 OLT via GPON's OMC channel and if required via TR-069. The AOLT in turn is managed with either Alphion's AEMS (Element Management System) that provides configuration, profile based provisioning, event and fault management and performance monitoring for the AONT, or with a 3rd party NMS via northbound interface.

# SPECIFICATIONS

## GPON Uplink interface

Standard:	Fully ITU-T G.984 and G.988 compliant
Line rate:	Downstream: 2.488 Gbps; Upstream: 1.244 Gbps
Connector:	SC/APC, single-mode-fiber; Labeled 'PON'
Link Budget:	28 dB (Class B+) ITU G.984.2 Amd1
Wavelength:	Transmit: 1310+/-20nm; Receive: 1490+/-10nm
Tx Output power:	+0.5 to +5.0 dBm mean launch power
Rx Sensitivity:	-27dBm (at 10 dB extinction ratio w/FEC off)
Rx Overload:	-8 dBm
Distance:	up to 60 km (depending on split ratio & fiber loss)
OLS/OTM:	G.984.2Amd2 incl. RX & TX power, dying gasp
TC layer:	AES (128-bit key), US and DS FEC RS(255,239)
DBA :	DBRu mode 0 and mode 1SR
GEM port-IDs:	up to 256, Flexible mapping between T-CONT & GEM port, Multicast GEM
T-CONT:	Type 1-5, up to 64, 8 queues per T-CONT

## Ethernet interfaces

Type:	Four GE ports; RJ-45 connectors CAT5E, 100m (328ft); labeled 'GE1', 'GE2', 'GE3' and 'GE4'
Standard:	IEEE 802.3, 802.3u, 802.3ab, IEEE 802.3az, 802.3x
Link	10/100/1000Base-T with rate and full/half-duplex auto-negotiation and MDI/MDIX auto-sensing
MTU size:	2,000 Byte maximum per IEEE802.3as

## Voice/Fax interfaces

Type:	Two POTS FXS ports
Connector:	RJ-11 connectors; Labeled 'POTS1' and 'POTS2'
FXS:	5 REN per port, loop start, balanced and unbalanced ringing, configurable tones, country specific impedance, DTMF dialing, CLIP, Hook flash detection, Metallic Loop Testing (MLT), etc.

## RF Video interface

Type:	75 ohm Coax F-connector
RF output level:	18 dB
Total RF output:	36 dBm

## Power

AC Adapter:	Input: 100-240VAC, 50/60Hz Output: 12VDC, 1.5A
DC Connector:	2-pin Barrel connector
Switch:	Power ON/OFF pushbutton on rear
Power (Max):	~13.5 watts
Battery Backup:	8-pin (4x2) 'UPS' connector for connecting Battery Backup power supply w/On Battery, Battery Low, Battery Fail and Battery Missing indication

## Physical

Temperature:	Operating: 0 °C to 50 °C, Storage: -40 °C to 65 °C
Humidity (RH):	5% to 95% non-condensing
Dimensions:	243mm (W) x 141mm (D) x 39mm (H)
Weight:	0.640kg (1.4 lbs.)
Mounting	Wall, table/desktop or under table/desk
LED Indicators:	12 LEDs - PWR, BAT, ALARM, WAN, DATA, LINK4, LINK3, LINK1, VOICE2, VOICE1, RF
Switches:	ON/OFF Pushbutton, Recessed RESET Pushbutton

## L2 Ethernet features

Bridging:	802.1d STP transparent bridging, 512 MAC table, MAC aging timer, UNI port MAC limit, MAC Filters
US Rate Limiting:	Broadcast/multicast, unknown multicast and DLF
VLAN model:	TR-156 1:1 & N:1, Transparent LAN Service (TLS)
VLANs:	4,095 VLANs (2-4094), Untagged, Priority tagged, Port based, 802.1q single tagged, 802.1ad (Q-in-Q) double tagged, VLAN ID translation
VLANs per port:	up to 32 configurable VLAN IDs per ONT/port
Multicast:	IGMPv2/v3 & MLDv2 snooping, 256 multicast groups, 8 clients, 32 simultaneous flows/client
QoS Classification:	US: 802.1p TCI, 802.1q CoS, per port IP ToS/DSCP to 802.1p mapping/re-marking; DS: per GEM port
QoS Scheduling:	SP, WRR, SP+WRR, 8 queues per T-CONT
Congestion:	PAUSE frame, tail-drop, rate-limiting per port
OAM:	Stats, PMs, GEM & UNI port loopback, 802.1ag*

## Gateway features for IPv4 and IPv6

WAN side:	PPPoE client, IPoE with DHCP client or static IP, NAT/NAPT, port forwarding, port triggering
LAN side:	DHCP server and relay agent, DHCP option 60, DNS relay
Routing:	RIP v1/v2 and static IP routing
IPv6 Mode:	Dual stack lite, 6rd

## Firewall

Type:	Stateful packet inspection (SPI) pass/block
Filtering:	DoS attack prevention, IP source/destination, TCP/UDP port source/destination, MAC source
ALGs:	FTP, SIP, H.323, RSTP
VPN:	PPTP, L2TP, IPsec pass-through
Access control:	DMZ, Parental Controls

## VoIP

Protocols:	SIP (RFC3261), SDP (RFC2327), RTP/RTCP (RFC3550, RFC3605), RFC3611*, RFC2198*, DTMF & Tones (RFC2833)
CLASS features:	Caller ID, call transfer, call forwarding, call hold, call park and pickup, call waiting, MWI, 3-way conference, etc.
Codec:	ITU-T G.711 ( $\mu$ & a-law), G.722, G.723.1, G.729a/b, echo cancellation, jitter buffer, voice activity detection (VAD), silence suppression, comfort noise generation (CNG), voice modem bypass
Fax:	ITU-T T.30, T.38 FoIP, Fax Relay, Fax by-pass
IP address:	DHCP client or static IP configuration
Interop (IOP):	Proven with major soft switch, gateways, IP-PBXs

## Secure Management

Local:	Web based GUI (HTTPS)
Remote:	G.984.4/988 OMCI, G.984 PLOAM, Telnet, TR-069
Authorization:	Secure ONT registration - ONT serial number, PLOAM password

## Regulatory Compliance

Certification:	CE mark (Conformité Européenne) Compliant
EMC/EMI Criteria:	EN300 386
EMC Emissions:	EN55022, CISPR-22 Class B
EMC Immunity:	Radiated RF: EN/IEC61000-4-3(2002) level 2 Conducted RF: EN/IEC61000-4-6(2001) level 2
Safety:	EN/IEC60950-1/UL60950
Laser Safety:	EC60825-1 Class 1 laser safety per G.664
Transient:	EN/IEC61000-4-4(2001) level 2
Surge:	EN/IEC61000-4-5(2001) 0.5 KV (line), 1.5 KV (earth)
ESD:	EN/IEC61000-4-2(2001) contact level 2, air level 3
Energy:	Broadband Equipment Code of Conduct (2013)
Environmental:	RoHS6, WEEE

\*Contact Sales for feature availability